

seca 664

Wireless Electronic wheelchair scales



- High capacity, up to 800 lbs.
- Flat platform with self-lowering ramp.
- Integrated pre-TARE function.
- Easy to fold together and transport.

seca 664:

Real comfort due to concentration on the essentials

Safety, functionality and aesthetic design – the seca 664 set standards in medical weighing. Specially designed for weighing wheelchair patients in rehabilitation centers, nursing homes, hospitals and in dialysis centers – this scale provides both its users and patients maximum comfort and safety.



High capacity and easy to mount ramp.

Due to the scale's load-bearing capacity of 800 lbs, weighing even heavy wheelchair patients is effortless with the seca 664. An extremely flat platform with an automatically lowered ramp ensure that the scale is easy to mount. The firmly installed side rails and a black ribbed rubber surface are additional safety features.

Integrated pre-TARE function.

With the pre-TARE function, the weight of the wheelchair can first be stored. Then, at the touch of a button, the weight of the wheelchair can be deducted from the total weight of the patient and wheelchair, thus automatically calculating the weight of the patient.

Easy to fold together and transport.

A rotatable LCD display with large figures is easy to read both for the patient and for the clinician. An important additional advantage is the mobility of the scale: the seca 664 can be folded together in no time at all and pushed along on its transport castors.



The platform's side rails keep a wheelchair safe and secure.



The seca 664 simply folds up and moves easily across the floor on castors.



seca 664

Technical Data

- Capacity: 800 lbs / 360 kg
- Graduation: 0.2 lbs / 100 g
- Dimensions (WxHxD):
43.4 x 35.9 x 45.3" /
1,102 x 912 x 1,150 mm
- Dimensions/platform (WxHxD):
29.9 x 2.2 x 36.6" / 760 x 55 x 930 mm
- Weight: 73.6 lbs / 33.4 kg
- Power supply: power adapter, rechargeable batteries
- Functions: TARE, pre-TARE, auto-HOLD, BMI, lbs/kg switch-over, damping, automatic switch-off
- Optional: RS232 interface seca 460